



Pole	Width /w	Pitch /p	Width /F	Width /B0	Qty. per reel	Reel qty. per carton	Qty. per carton
2P	32mm	16mm	14.25mm	18.11mm	200	8	1600
3~9P	56mm	20mm	26.25mm	40.97mm	200	5	1000
10~12P	72mm	16mm	34.25mm	59.47mm	180	3	540

REV	ECN	DESCRIPTION	DRAFT	DATE
T1	17-0159	Change the drawing and tolerance table	YU-ZH	2020.05.26
T2	17-0015	Add engrave Design Change	LY	2019.05.29
T3	17-0015	Design Change	CWZ	2017.02.09

UL Standard: B

额定电压/Rated Voltage(V)/Current(A): 300/8

IEC 标准/IEC Standard: II/2

IEC 标准/IEC Standard: II/2

过压类别/Overvoltage Category/污染等级: II/2

额定电压/电涌/Rated Voltage(V)/Current(A): 250/8

额定浪涌电压(KV)/Rate Impulse Voltage(KV): 2.5

间距/Pitch(mm)/线数范围/Poles: 3.50/N=02~12P

使用温度范围/Operating temperature(°C): -40~+130

符合RoHS环保要求/Conform to RoHS: Yes

材料: /

表面: /

APPD: Lan CHH 2020.05.26

NAME: 宁波高松电子有限公司 NINGBO DEGSON ELECTRICAL CO., LTD

15EDGVC/M-THR-3.5-XXP-1Y-00A(H)

DRAWING NO.: 15EDGVC/M-THR-3.5-C02

SCALE: 1:1

SHEET 1/1

尺寸/英寸	0	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36	37	38	39	40	41	42	43	44	45	46	47	48	49	50
尺寸/英寸	0	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36	37	38	39	40	41	42	43	44	45	46	47	48	49	50