



尺寸 (mm)	公差 (mm)
0	±0.1
1	±0.1
2	±0.1
3	±0.1
4	±0.1
5	±0.1
6	±0.1
7	±0.1
8	±0.1
9	±0.1
10	±0.1
11	±0.1
12	±0.1
13	±0.1
14	±0.1
15	±0.1
16	±0.1
17	±0.1
18	±0.1
19	±0.1
20	±0.1
21	±0.1
22	±0.1
23	±0.1
24	±0.1
25	±0.1
26	±0.1
27	±0.1
28	±0.1
29	±0.1
30	±0.1
31	±0.1
32	±0.1
33	±0.1
34	±0.1
35	±0.1
36	±0.1
37	±0.1
38	±0.1
39	±0.1
40	±0.1
41	±0.1
42	±0.1
43	±0.1
44	±0.1
45	±0.1
46	±0.1
47	±0.1
48	±0.1
49	±0.1
50	±0.1
51	±0.1
52	±0.1
53	±0.1
54	±0.1
55	±0.1
56	±0.1
57	±0.1
58	±0.1
59	±0.1
60	±0.1
61	±0.1
62	±0.1
63	±0.1
64	±0.1
65	±0.1
66	±0.1
67	±0.1
68	±0.1
69	±0.1
70	±0.1
71	±0.1
72	±0.1
73	±0.1
74	±0.1
75	±0.1
76	±0.1
77	±0.1
78	±0.1
79	±0.1
80	±0.1
81	±0.1
82	±0.1
83	±0.1
84	±0.1
85	±0.1
86	±0.1
87	±0.1
88	±0.1
89	±0.1
90	±0.1
91	±0.1
92	±0.1
93	±0.1
94	±0.1
95	±0.1
96	±0.1
97	±0.1
98	±0.1
99	±0.1
100	±0.1

ITEM	NAME OF PART	MATERIAL	NOTES
1	Housing	PA66	UL94V-0
2	COVER	PA66	UL94V-0
3	Screw1	Steel	M3/In. Plated
4	Cage	Copper alloy	Ni Plated
5	Pin	Copper	Sn Plated
6	Screw2	Steel	M2.5/In. Plated

UL 标准 / UL Standard:	B	C	D
额定电压 / Rated Voltage (V) / Current (A)	300/15	/	300/10
IEC 标准 / IEC Standard:			
过压类别 / Over-voltage Category / 污染等级 / Pollution Degree	III/3	III/2	II/2
额定电压 / 电流 / Rated Voltage (V) / Current (A)	/	400/20	/
额定脉冲电压 (KV) / Rate Impulse Voltage (KV)	/	4	/
额定扭矩 / Torque Tightening (kg*cm)	M3: 6		
导线范围 (硬导线/软线) / Wire Range (rigid and flexible) (mm <sup>2</sup> /AWG)	0.2~2.5 / 28~12		
间距 / Pitch (mm) / 极数 / Poles	7.62 / N=02~16P		
剥线长度 / Stripping length (mm)	7~8		
使用温度范围 / Operating Temperature (°C)	-40~+105		
符合 RoHS 环保要求 / Conform to RoHS	Yes		

MATERIAL: / SURFACE: /

**NINGBO DESON ELECTRICAL CO., LTD**  
 宁波得森电子有限公司  
 NAME: ZEDGKRM-7.62-XXP-1Y-00A(H)  
 DRAWING NO.: 10002066  
 REV: TO  
 TYPE: CUSTOMER DRAWING  
 SCALE: 2.5:1 SHEET: 1/1

REV	EON	DESCRIPTION	DRT	DATE
1				
2				
3				
4				
5				
6				
7				