



| 公差等级/General Tolerances(mm) | |
|-----------------------------|--------|
| 0 | >3 |
| ~ | >6 |
| 3 | >10 |
| 6 | >18 |
| 10 | >30 |
| ±0.12 | >50 |
| ±0.18 | >80 |
| ±0.22 | >120 |
| ±0.26 | >180 |
| ±0.31 | >250 |
| ±0.37 | >315 |
| ±0.45 | >400 |
| ±0.57 | >500 |
| ±0.80 | >630 |
| ±0.93 | >800 |
| ±1.05 | >1000 |
| ±1.15 | >1250 |
| ±1.60 | >1600 |
| ±2.20 | >2000 |
| ±2.50 | >2500 |
| ±Z | 0.1/10 |

| | | | |
|--|---------------|----------|-----------|
| 3 | Cover | PC | UL94V-2 |
| 2 | Metals | Steel | Sn plated |
| 1 | Housing | PC | UL94V-2 |
| ITEM | NAME OF PART | MATERIAL | NOTES |
| UL 标准 | UL Standard: | B | C |
| 额定电压/电涌/Rated Voltage(V)/Current(A) | 600/15 | / | / |
| IEC 标准/IEC Standard: | | | |
| 过压类别/Overvoltage Category/污染等级/Pollution Degree | III/3 | III/2 | II/2 |
| 额定电压/电涌/Rated Voltage(V)/Current(A) | / | 450/24 | / |
| 工频耐压/Withstanding Voltage(V/Min) | / | AC2500 | / |
| 线径范围(硬线和软线)/Wire Range(rigid and flexible)(mm ² /AWG) | 0.5~2.5/22~14 | | |
| 间距/Pitch(mm)/线数范围/Poles | 3.5/05P | | |
| 铜线长度/Stripping length(mm) | 10~13 | | |
| 使用温度范围/Operating temperature(°C) | -40~+85 | | |
| 符合RoHS环保要求/Conform to RoHS | Yes | | |

MATERIAL: /

SURFACE: /

MAT NO.: /

STATUS: /

APPD: LIGL 2020.06.03

CHKD: Mek 2020.06.03

DRT: LuoXM 2020.06.03

DEGSON® NINGBO DEGSON ELECTRICAL CO., LTD
宁波高松电子有限公司

NAME: **DG228-3.5-05P-1Y-00A(H)**

DRAWING NO.: DG228-3.5-C05

TYPE: CUSTOMER DRAWING



SIZE: A4

mm
inch

SCALE: 2.5:1 SHEET

REV T2

1/1

REV ECN DESCRIPTION

DRT

DATE

SIZE: A4

mm
inch

TYPE: CUSTOMER DRAWING

REV T2

1/1