



公差/公差 (General Tolerances)(mm)	0	>3	>6	>10	>18	>30	>50	>80	>120	>180	>250	>315	>400	0.1/10
±0.12	±0.18	±0.22	±0.31	±0.37	±0.57	±0.80	±0.93	±1.05	±1.15	±1.60	±2.20	±2.50	±2.80	±2

UL 标准/UL Standard:	B	C	D
额定电压/电流/Rated Voltage(V)/Current(A)	300/15	/	300/10
过压类别/Overvoltage Category/污染等级	III/3	III/2	II/2
级/Pollution Degree	III/3	III/2	II/2
额定电压/电流/Rated Voltage(V)/Current(A)	400/20	400/20	1000/20
额定冲击电压(kV)/Rate Impulse Voltage(kV)	4	4	4
间距/Pitch(mm)/线数/导线/Poles	7.62/N=02~16P		4
使用温度范围/Operating Temperature(°C)	-40~+105		Yes
符合环保要求/Conform to RoHS			Yes
标准颜色/Standard color number:			/
标准颜色/Standard color number:	PANTONE / RAL		/

ITEM	NAME OF PART	MATERIAL	NOTES
3	Clamp	Copper alloy	Sn Plated
2	Cover	PA66	UL94V-0
1	Housing	PA66	UL94V-0

SURFACE: /

MATERIAL: /

MAT NO.: /

STATUS: /

APPD: Li GL 2020.06.17

CHKD: Moo J 2020.06.17

DRAFT:Wang Y2 2020.06.17

NAME: **DEGSON** 宁波高松电子有限公司
NINGBO DEGSON ELECTRICAL CO., LTD

2EDGB-7.62-XXP-14-00A(H)

DRAWING NO.: 2EDGB-7.62-C01

TYPE: CUSTOMER DRAWING

SCALE: 2:1 SHEET 1/1

REV	ECN	DESCRIPTION	DRAFT	DATE