



公差/General tolerances(mm)		0	>3	>6	>10	>18	>30	>50	>80	>120	>180	>250	>315	>400	0.1/10
±0.12	+0.18	±0.22	±0.26	±0.31	±0.37	±0.57	±0.80	±0.93	±1.05	±1.15	±1.60	±2.20	±2.50	±500	±#2

ITEM	NAME OF PART	MATERIAL	NOTES
4	Short Pin	Copper	Sn plated
3	Long Pin	Copper	Sn plated
2	Cover	PA66	UL94V-0
1	Housing	PA66	UL94V-0

UL 标准/UL Standard:	B	C	D
额定电压/Rated Voltage(V)/Current(A)	300/15	/	300/10
IEC 标准/IEC Standard:			
过压类别/Overvoltage Category/污染等	III/2		
额定电压/电涌/Rated Voltage(V)/Current(A)	320/10		
额定脉冲电压(KV)/Rate Impulse Voltage(KV)	4		
间距/Pitch(mm)/线数范围/Poles	5.08/N=0~48P		
使用温度范围/Operating temperature(°C)	-40~+105		
符合RoHS环保要求/Conform to RoHS	Yes		

SURFACE: /

MATERIAL: /

MAT NO.: /

STATUS: /

APPD: LanChH 2020.05.19

CHKD: GongYzh 2020.05.19

DRFT: CenSL 2020.05.19

NINGBO DEGSON ELECTRICAL CO., LTD

2EDGRH-5.08-XXP-1Y-00A(H)

DRAWING NO.: 2EDGRH-5.08-C01

TYPE: CUSTOMER DRAWING

REV	ECN	DESCRIPTION	DRFT	DATE	SIZE: A4	SCALE: 1:1	REV	T1
1					mm		1/1	