



精度等级/General	公差值(mm)
0	>30
1	>10
2	>3
3	>1.0
4	>0.5
5	>0.3
6	>0.2
7	>0.15
8	>0.1
9	>0.075
10	>0.05
11	>0.0375
12	>0.025
13	>0.01875
14	>0.0125
15	>0.009375
16	>0.00625
17	>0.0046875
18	>0.003125
19	>0.00234375
20	>0.00171875
21	>0.001275
22	>0.00095625
23	>0.0007171875
24	>0.0005378125
25	>0.000403125
26	>0.00030234375
27	>0.000226875
28	>0.0001703125
29	>0.0001278125
30	>0.0000959375
31	>0.000071953125
32	>0.00005396875
33	>0.000040478125
34	>0.000030359375
35	>0.00002276875
36	>0.00001708125
37	>0.0000128125
38	>0.00009609375
39	>0.000072071875
40	>0.0000540546875
41	>0.00004054125
42	>0.00003040625
43	>0.0000228046875
44	>0.000017103125
45	>0.000012828125
46	>0.0000962109375
47	>0.000072158125
48	>0.00005411875
49	>0.00004058125
50	>0.000030436875
51	>0.0000228353125
52	>0.0000171346875
53	>0.000012859375
54	>0.000096440625
55	>0.000072384375
56	>0.000054291875
57	>0.000040753125
58	>0.00003060875
59	>0.0000229071875
60	>0.000017205625
61	>0.0000128803125
62	>0.000096650625
63	>0.000072571875
64	>0.000054423125
65	>0.0000408846875
66	>0.0000307403125
67	>0.00002303875
68	>0.000017234375
69	>0.0000129090625
70	>0.000096860625
71	>0.000072793125
72	>0.000054575625
73	>0.0000410371875
74	>0.0000308928125
75	>0.00002319125
76	>0.00001725875
77	>0.0000129334375
78	>0.000097070625
79	>0.000072996875
80	>0.000054701875
81	>0.000041193125
82	>0.0000310483125
83	>0.000023291875
84	>0.000017283125
85	>0.0000129576875
86	>0.000097280625
87	>0.000073198125
88	>0.000054833125
89	>0.0000412546875
90	>0.00003110375
91	>0.000023390625
92	>0.0000173071875
93	>0.000012981875
94	>0.000097490625
95	>0.000073403125
96	>0.000054965625
97	>0.0000413101875
98	>0.00003115875
99	>0.0000234890625
100	>0.00001733125

5	Nut	Copper alloy	
4	Pin header 2	Copper	Sn Plated
3	Pin header 1	Copper	Sn Plated
2	Cover	PA66	UL94V-0
1	Housing	PA66	UL94V-0
ITEM	NAME OF PART	MATERIAL	NOTES
UL 标准 / UL Standard:	B	C	D
额定电压 / Rated Voltage(V)	300/15	300/10	
过流类别 / Overcurrent Category / 过流率	III/3	III/2	II/2
额定电流 / Rated Current(A)	320/20		
额定电压 / Rated Voltage(V)	320/20		
额定冲击电压 / Rated Impulse Voltage (kV)	4		
额定浪涌电流 / Rated Surge Current (A)	N=04~48P		
额定温度范围 / Operating Temperature(°C)	-40~+105		
符合RoHS指令要求 / Conform to RoHS	Yes		

MATERIAL:	/
MAT NO.:	/
STATUS:	/
APPD:	Lan CHH 2020.05.18
CHKD:	/
DRT:	ZhongX 2017.03.28
NAME:	NINGBO DESSON ELECTRICAL CO., LTD
DRAWING NO.:	ZEDGVTM-5.08-001
TYPE:	CUSTOMER DRAWING
SCALE:	2:1
SHEET:	1/1