









未标尺寸请参考3D文件

Pitch Range		In mm				Nominal Dimension				Range In mm			
Over	6	Over	10	Over	30	Over	60	Over	100	Over	150		
TO	6	TO	10	TO	30	TO	60	TO	100	TO	150	0.1/10	
	10		24		30		60		100		150		±2°
	±0.15		±0.20		±0.30		±0.30		±0.50		±0.70		±1.00
													±1.30
													±2°



5	Spring	Stainless steel	
4	Clamp	Copper alloy	Sn plated
3	Cover	PA66	UL94V-0
2	housing 2	PA66	UL94V-0
1	housing 1	PA66	UL94V-0

ITEM	NAME OF PART	MATERIAL	NOTES
UL 标准/UL Standard:		B	C
额定电压/电涌/Rated Voltage(V)/Current(A)		300/151	150/151
IEC 标准/IEC Standard:			
过压类别/Overvoltage Category/污染等级/Pollution Degree		III/3	III/2
额定电压/电涌/Rated Voltage(V)/Current(A)		320/20	/
额定脉冲电压(kV)/Rate Impulse Voltage(kV)		4	/
线径范围(硬线和软线)/Wire Range(rigid and flexible)(mm ² /AWG)		0.2~2.5/22~14	/
剥线长度/Stripping length(mm)		5.0/N=02~24P	/
使用温度范围/Operating temperature(°C)		9~10	/
符合RoHS环保要求/Conform to RoHS		-40~+105	/
标准颜色编号/Standard color number:		Yes	/
PANTONE		PANTONE 428C	/

MATERIAL: /

MAT NO.: /

STATUS: /

APPD: /

CHKD: /

DRT: YHG 2011.04.27

SIZE: A4

TYPE: CUSTOMER DRAWING

DEGSON® 宁波高松电子有限公司
NINGBO DEGSON ELECTRICAL CO., LTD

NAME: 8EDGKF-5.0-XXP-11-01A(H)

DRAWING NO.: 8EDGKF-5.0-C03

SCALE: 1:1

REV T0
SHEET 1/1

1 2 3 4 5 6