



公差等级/General Tolerances(mm)	
0	>3
~	>6
3	>10
6	>18
10	>30
18	>50
30	>80
50	>120
80	>180
120	>250
180	>315
250	>400
315	>500
400	>500
500	>500
±0.12	±0.18
±0.22	±0.26
±0.31	±0.37
±0.57	±0.80
±0.93	±1.05
±1.15	±1.60
±2.20	±2.50
±Z	±Z

ITEM	NAME OF PART	MATERIAL	NOTES
1	Housing	PA66	UL94V-0
2	Pin	Copper Alloy	Sn Plated

UL 标准/UL Standard:	B	C	D
额定电压/电涌/Rated Voltage(V)/Current(A)	150/4	150/4	150/4
IEC 标准/IEC Standard:	过压类别/Overvoltage Category/污染等级		
污染等级/Pollution Degree	III/3	III/2	II/2
额定电压/电涌/Rated Voltage(V)/Current(A)	130/6	/	/
额定电涌电压(KV)/Rate Impulse Voltage(KV)	2.5	/	/
间距/Pitch(mm)/线数/极数/Poles	2.50/N=02~12P	/	/
使用温度范围/Operating Temperature(°C)	-40~+105	/	/
符合RoHS环保要求/Conform to RoHS	Yes	/	/
标准颜色编号/Standard color number:	PANTONE 7534U	/	/
PANTONE /RAL	/	/	/

MATERIAL:	/	SURFACE:	/
MAT NO.:	/		
STATUS:	/		
APPD:			
CHKD:			
NAME:	DEGSON® NINGBO DEGSON ELECTRICAL CO., LTD		
DRAWING NO.:	10001567		
TYPE:	CUSTOMER DRAWING		
SCALE:	4:1		
REV	T0	REV	T0
SHEET	1/1	SHEET	1/1

REV	ECN	DESCRIPTION	DRAFT	DATE	SIZE: A4	TYPE: CUSTOMER DRAWING	SCALE: 4:1	REV	T0