

公差等级/General	tolerance/(mm)	0	>3	>6	>10	>18	>30	>50	>80	>120	>180	>280	>315	>400	>500	0.1/10
±0.12	±0.18	±0.22	±0.26	±0.31	±0.37	±0.57	±0.80	±0.93	±1.05	±1.15	±1.60	±2.20	±2.50	±2.50	±Z	±Z

2	Pin	Copper	Sn Plated
1	Housing	PA66	UL94V-0
ITEM	NAME OF PART	MATERIAL	NOTES
UL 标准 /UL Standard:	B	C	D
额定电压/电压/Rated Voltage(V)/Current(A)	300/15	/	300/10
IEC 标准 /IEC Standard:			
过压类别/Overvoltage Category/污染等级	III/3	/	/
被/ Pollution Degree			
额定电压/电压/Rated Voltage(V)/Current(A)	400/20	/	/
额定电涌电压(KV)/Rate Impulse Voltage(KV)	4	/	/
额定电涌电压(KV)/Rate Impulse Voltage(KV)	7.50/N=02~12P	/	/
使用温度范围/Operating Temperature(°C)	-40~+105	/	/
符合RoHS标准/Conform to RoHS	Yes	/	/
标准颜色编号/Standard color number:			
PANTONE / RAL	PANTONE 7534U		

MATERIAL: / SURFACE: /

MAT NO.: /

STATUS: /

APPD: /

CHKD: /


DRAFT: CenX 2020.06.02

SIZE: A4

TYPE: CUSTOMER DRAWING

**DEGSON® NINGBO DEGSON ELECTRICAL CO., LTD**  
 宁波高松电子有限公司  
 8EDGVCB-7.5-XXP-11-01A(H)

REV	ECN	DESCRIPTION	DRAFT	DATE



A B C D

1 2 3 4 5 6

D B A