



公差等级/General Tolerances(mm)		公差等级/General Tolerances(mm)										公差等级/General Tolerances(mm)	
0	>3	>6	>10	>18	>30	>50	>80	>120	>180	>280	>315	>400	0.1/10
~	~	~	~	~	~	~	~	~	~	~	~	~	~
3	6	10	18	30	50	80	120	180	280	315	400	500	~
±0.12	±0.18	±0.22	±0.26	±0.31	±0.37	±0.57	±0.80	±0.93	±1.05	±1.15	±1.60	±2.20	±2.50
													±Z

ITEM	NAME OF PART	MATERIAL	NOTES
4	Pin header	Copper alloy	Sn plated
3	Screw	Steel	M3/Zn plated
2	Cage	Copper alloy	M3/Ni plated
1	Housing	PA66	UL94V-0

UL 标准/UL Standard:	B	C	D
额定电压/Rated Voltage(V)	300	15	300/10
IEC 标准/IEC Standard:			
过压类别/Overvoltage Category/污秽等级/Pollution Degree	III/3	III/2	II/2
额定电压/电流/Rated Voltage(V)/Current(A)	/	250/24	/
工频耐压/Withstanding voltage(V/Min)	/	AC2000	/
拧紧扭矩/Torque Tightening(N·m/Lbin)	/	M3, 0.5/4.43	/
线径范围/导线和线径/Wire Range(rigid and flexible)(mm²/AWG)	0.5~2.5/24~14		
可剥长度/Stripping length(mm)	5.08/N=02~24P		
使用温度范围/Operating temperature(°C)	-40~+105		
符合RoHS环保要求/Conform to RoHS	Yes		

MATERIAL:	SURFACE: /
MAT NO.:	/
STATUS:	/

NAME:	NAME:
APPD: Li GL 2020.06.22	NINGBO DEGSON ELECTRICAL CO., LTD
CHKD: Moo J 2020.06.22	DG104-5.08-XXP-1Y-00A(H)

DRAWING NO.:	SCALE:
DG104-5.08-XXP-1Y-00A(H)	2:1
TYPE: CUSTOMER DRAWING	SHEET
REV: T0	1/1

REV	ECN	DESCRIPTION	DRAFT	DATE	SIZE	SCALE	SHEET
1					A4	2:1	1/1

REV	ECN	DESCRIPTION	DRAFT	DATE	SIZE	SCALE	SHEET
1					A4	2:1	1/1