



未注公差/General Tolerances(mm)	
0	>3
~	6
±0.12	±0.18
±0.22	±0.26
±0.31	±0.37
±0.57	±0.80
±1.05	±1.15
±1.60	±2.20
±2.50	
>5	>10
>10	>18
>18	>30
>30	>50
>50	>80
>80	>120
>120	>180
>180	>250
>250	>315
>315	>400
>400	>500
>500	
0.1/10	
EZ	

5	Pin header	Copper alloy	Sn Plated
4	Cage	Copper alloy	M2.5/Ni Plated
3	Screw	Steel	M2.5/Zn Plated
2	Cover	PA66	UL94V-0
1	Housing	PA66	UL94V-0
ITEM	NAME OF PART	MATERIAL	NOTES
UL 标准/UL Standard: B C D			
额定电压/电流/Rated Voltage(V)/Current(A) 300/16 / /			
IEC 标准/IEC Standard: / / /			
过压类别/Overvoltage Category/污染等级 III/3 III/2 II/2			
额定电压/电流/Rated Voltage(V)/Current(A) 250/18 320/18 630/18			
额定脉冲电压(KV)/Rate Impulse Voltage(KV) 4.0 4.0 4.0			
螺丝扭矩/Torque Tightening(N·m/Lb·in) M2.5, 0.4/3.54			
线缆范围(硬线和软线)/Wire Range(rigid and flexible)(mm ² /AWG) 0.5~2.5/26~12			
间距/Pitch(mm)/线数范围/Poles 5.08/N=02~24P			
剥线长度/Stripping length(mm) 6~7			
使用温度范围/Operating temperature(°C) -40~+105			
符合RoHS环保要求/Conform to RoHS Yes			
SURFACE: /			

MATERIAL:	/
MAT NO.:	/
STATUS:	/
APPD: Lon CHH	2022.03.18
CHKD: Chen Zh	2022.03.18
DRAFT: Gong XT	2022.03.18
NAME:	宁波高松电子有限公司 NINGBO DEGSON ELECTRICAL CO., LTD
DRAWING NO.:	DG125-5.08-C01
TYPE:	CUSTOMER DRAWING
SCALE:	1:1
REV	TO
1/1	1/1

REV	ECN	DESCRIPTION	DRAFT	DATE
1				
2				
3				
4				

SIZE: A4	mm	inch
TYPE: CUSTOMER DRAWING	SCALE: 1:1	SHEET 1/1