



公差/General Tolerances(mm)		公差/General Tolerances(mm)										公差/General Tolerances(mm)	
0	>3	>6	>10	>18	>30	>50	>80	>120	>180	>250	>315	>400	0.1/1.0
~	~	~	~	~	~	~	~	~	~	~	~	~	~
±0.12	±0.18	±0.22	±0.26	±0.31	±0.37	±0.57	±0.80	±0.93	±1.05	±1.15	±1.60	±2.20	±2.50
												±Z	

ITEM	NAME OF PART	MATERIAL	NOTES
5	Pin Header 2	Copper	Sn Plated
4	Pin Header 1	Copper Alloy	Sn Plated
3	Screw	Steel	M3/Zn Plated
2	Cage	Copper Alloy	M3/Ni Plated
1	Housing	PA66	UL94V-0

UL 标准/UL Standard:	B	C	D
额定电压/电压/Rated Voltage(V)/Current(A)	300/20	/	300/10
IEC 标准/IEC Standard:	450/20		
额定电压/电压/Rated Voltage(V)/Current(A)	450/20		
工频耐压/Withstanding Voltage(V/1MIN)	AC2000		
拧紧扭矩/Torque Tightening(N·m/Lb·in)	M3, 0.5/4.43		
线芯范围(硬线和软线)/Wire Range(rigid and flexible)(mm ² /AWG)	0.5~2.5/26~12		
剥线长度/Stripping length(mm)	5.0/N=0~48P		
使用温度范围/Operating Temperature(°C)	-40~+105		
符合RoHS要求/Conform to RoHS	Yes		

MATERIAL: / SURFACE: /

MAT NO.: /
 STATUS: /
 APPD: Lan CHH 2020.05.16
 CHKD: Yu JZh 2020.05.16
 DRT: CenK 2020.05.16

NAME: **DEGSON® NINGBO DEGSON ELECTRICAL CO., LTD**
DG130A-5.08-XXP-1Y-00A(H)

DRAWING NO.: 10002019
 TYPE: CUSTOMER DRAWING
 SCALE: 2:1
 SHEET 1/1

REV	ECN	DESCRIPTION	DRT	DATE
1				
2				
3				
4				