



公差带/General	tolerance(mm)	0	>3	>6	>10	>18	>30	>50	>80	>120	>180	>250	>315	>400	>500	>700	>1000
~	~	~	~	~	~	~	~	~	~	~	~	~	~	~	~	~	~
±0.12	±0.18	±0.22	±0.26	±0.31	±0.37	±0.57	±0.80	±0.93	±1.05	±1.15	±1.60	±2.20	±2.50	±3.00	±4.00	±5.00	±7.00

2	Pin header	Copper alloy	Sn Plated
1	Housing	PA66	UL94V-2
ITEM	NAME OF PART	MATERIAL	NOTES
UL 标准/UL Standard:		B	C
额定电压/电涌/Rated Voltage(V)/Current(A)		300/15	300/10
EC 标准/EC Standard:			
额定电压/电涌/Rated Voltage(V)/Current(A)			
额定电压/电涌/Rated Voltage(V)/Current(A)		630V/24A	
额定电压/电涌/Rated Voltage(V)/Current(A)		AC3000	
额定电压/电涌/Rated Voltage(V)/Current(A)		N=02~19P	
使用温度范围/Operating temperature(°C)		-40~+75	
符合RoHS环保要求/Conform to RoHS		Yes	

SURFACE:

MATERIAL: /  
 MAT NO.: /  
 STATUS: /  
 APPD: Lon CHH 2020.05.18  
 CHKD: /  
 DRT: jiangX 2013.03.12

NAME: **DEGSON** 宁波高松电子有限公司  
 NINGBO DEGSON ELECTRICAL CO., LTD

DRAWING NO.: 10002005  
 TYPE: CUSTOMER DRAWING  
 SCALE: 2.5:1  
 SHEET 1/1

REV	ECN	DESCRIPTION	DRT	DATE
1				

1 2 3 4 5 6