



精度等级/General	tolerance(mm)	0	>3	>6	>10	>18	>30	>50	>80	>120	>180	>250	>315	>400	>500	0.1/10
~	~	~	~	~	~	~	~	~	~	~	~	~	~	~	~	±Z
±0.12	±0.18	±0.22	±0.26	±0.31	±0.37	±0.57	±0.80	±0.93	±1.05	±1.15	±1.60	±2.20	±2.50			

4	Spring	Stainless steel	
3	Pin header	Copper Alloy	
2	Button	PA66	
1	Housing	PA4T	
ITEM	NAME OF PART	MATERIAL	NOTES
UL 标准/UL Standard:	B	C	D
额定电压/电涌/Rated Voltage(V)/Current(A)	300/12	/	300/10
IEC 标准/IEC Standard:			
过压类别/Overvoltage Category/污染等	II/2	III/2	III/3
额定电压/电涌/Rated Voltage(V)/Current(A)	320/17.5	200/17.5	200/17.5
额定脉冲电压(KV)/Rate Impulse Voltage(KV)	2.5	2.5	2.5
线径范围(硬线和软线)/Wire Range(rigid and flexible)(mm ² /AWG)	0.2~1.5/28~14		
间距/Pitch(mm)/线数范围/Poles	3.50/N=02~24P		
剥线长度/Stripping length(mm)	8~9		
使用温度范围/Operating temperature(°C)	-40~+130		
符合RoHS环保要求/Conform to RoHS	Yes		

MATERIAL: /
SURFACE: /

MAT NO.: /
STATUS: /
APPD: LIQL 2020.05.15
CHKD: Mek 2020.05.15
DRAFT: LuoXM 2020.05.15

NAME: **DEGSON® NINGBO DEGSON ELECTRICAL CO., LTD**
宁波高松电子有限公司
DRAWING NO.: 10000989

TYPE: CUSTOMER DRAWING
SCALE: 1:1
REV T0
1/1

REV	ECN	DESCRIPTION	DRAFT	DATE



SIZE: A4
mm/inch
TYPE: CUSTOMER DRAWING
SCALE: 1:1
REV T0
1/1