






公差等级/General	tolerance(mm)	0	>3	>6	>10	>18	>30	>50	>80	>120	>180	>250	>315	>400	>500	0.1/10
~	~	~	~	~	~	~	~	~	~	~	~	~	~	~	~	±Z
±0.12	±0.18	±0.22	±0.26	±0.31	±0.37	±0.57	±0.80	±0.93	±1.05	±1.15	±1.60	±2.20	±2.50	±2.50	±Z	±Z



4	Cover	PA66	UL94V-0
3	Pin Header	Copper	Sn Plated
2	Spring	Stainless steel	/
1	Housing	PA66	UL94V-0
ITEM	NAME OF PART	MATERIAL	NOTES

UL 标准	UL Standard:	B	C	D
额定电压/电涌/Rated Voltage(V)/Current(A)	300/30	/	/	/
IEC 标准/IEC Standard:				
过压类别/Overvoltage Category/污染等级/Pollution Degree	III/3	III/2	II/2	
额定电压/电涌/Rated Voltage(V)/Current(A)	500/32	630/32	1000/32	
额定脉冲电压/Rate Impulse Voltage(KV)	6	6	6	
线径范围(硬线和软线)/Wire Range(rigid and flexible)(mm²/AWG)	0.2~4/24~10			
间距/Pitch(mm)/线数范围/Poles	7.5/N=01~16P			
剥线长度/Stripping length(mm)	10~11			
使用温度范围/Operating temperature(°C)	-40~+105			
符合RoHS环保要求/Conform to RoHS	Yes			

MATERIAL: / SURFACE: /

MAT NO.: /  
 STATUS: /  
 APPD: Li GL 2020.06.13  
 CHKD: Ma EK 2020.06.13

NAME: **DEGSON® NINGBO DEGSON ELECTRICAL CO., LTD**  
**DG260-7.5-XXP-1Y-00A(H)**

DRAWING NO.: DG260-7.5-C01  
 TYPE: CUSTOMER DRAWING  
 SCALE: 1.5:1 SHEET 1/1

REV	ECN	DESCRIPTION	DRAFT	DATE