



公差等级/General	tolerance/(mm)	0	>3	>6	>10	>18	>30	>50	>80	>120	>180	>250	>315	>400	>500	0.1/10
~	~	~	~	~	~	~	~	~	~	~	~	~	~	~	~	±Z
±0.12	±0.18	±0.22	±0.26	±0.31	±0.37	±0.57	±0.80	±0.93	±1.05	±1.15	±1.60	±2.20	±2.50			

5	Pin header	Copper alloy	Sn plated
4	Cage	Copper alloy	M2.5/Ni Plated
3	Screw	Steel	M2.5/Zn Plated
2	Cover	PA66	UL94V-0
1	Housing	PA66	UL94V-0

  

UL 标准/UL Standard:	B	C	D
额定电压/电涌/Rated Voltage(V)/Current(A)	300/15	/	300/10
IEC 标准/IEC Standard:			
过压类别/Overvoltage Category/污染等级	III/3	III/2	II/2
绝缘/Insulation Degree	/	250/24	/
额定电压/电涌/Rated Voltage(V)/Current(A)	/	AC2000	/
工频耐压/Withstanding Voltage(V/Min)	/	M2.5, 0.4/3.5/4	/
转矩/扭距/Torque Tightening(N·m/Lb·in)	/	0.5~2.5/28~12	/
线径范围(硬线和软线)/Wire Range(rigid and flexible)(mm²/AWG)	/	5.0/N=02~20P	/
剥线长度/Stripping length(mm)	/	5~6	/
使用温度范围/Operating temperature(°C)	/	-40~+105	/
符合RoHS环保要求/Conform to RoHS	/	Yes	/

**DEGSON** 宁波高松电子有限公司  
NINGBO DEGSON ELECTRICAL CO., LTD

NAME: DG632-5.0-XXP-1Y-00A(H)

MATERIAL:	/
MAT NO.:	/
STATUS:	/
APPD:	Li GL 2020.06.19
CHKD:	Moo J 2020.06.19
DRT:	Lin 2007.03.22

DRAWING NO.:	DG632-5.0-C01
TYPE:	CUSTOMER DRAWING
SCALE:	3:1
REV	TO
1/1	1/1

REV	ECN	DESCRIPTION	DRT	DATE