



5	Pin header	Copper alloy	Sn plated
4	Cage	Copper alloy	M2.5/Ni Plated
3	Screw	Steel	M2.5/Zn Plated
2	Cover	PA66	UL94V-0
1	Housing	PA66	UL94V-0

UL 标准/UL Standard:	B	C	D
额定电压/电涌/Rated Voltage(V)/Current(A)	300/15	/	300/10
IEC 标准/IEC Standard:			
过压类别/Overvoltage Category/污秽等级/Pollution Degree	III/3	III/2	II/2
额定电压/电涌/Rated Voltage(V)/Current(A)	/	250/24	/
工频耐压/Withstanding Voltage(V/Min)	/	AC2000	/
拧紧扭矩/Torque Tightening(N·m/Lb.in)	M2.5: 0.4/3.54		
线径范围(硬线和软线)/Wire Range(rigid and flexible)(mm²/AWG)	0.5~2.5/28~12		
间距/Pitch(mm)/线数范围/Poles	5.0/N=02~20P		
剥线长度/Stripping length(mm)	5~6		
使用温度范围/Operating temperature(°C)	-40~+105		
符合RoHS环保要求/Conform to RoHS	Yes		

NINGBO DEGSON ELECTRICAL CO., LTD
 宁波高松电子有限公司

NAME: **DG632-5.0-XXP-1Y-00A(H)**

MATERIAL:	/
MAT NO.:	/
STATUS:	/
APPD:	LI GL 2020.06.19
CHKD:	Moo J 2020.06.19
DRAFT:	Lin 2007.03.22
DRAWING NO.:	DG632-5.0-C01
TYPE:	CUSTOMER DRAWING
SCALE:	3:1
REV	TO
REV	1/1

REV	ECN	DESCRIPTION	DRAFT	DATE