




公差等级/General	tolerance/(mm)	0	>3	>6	>10	>18	>30	>50	>80	>120	>180	>250	>315	>400	>500	0.1/10
~	~	~	~	~	~	~	~	~	~	~	~	~	~	~	~	±Z
±0.12	±0.18	±0.22	±0.26	±0.31	±0.37	±0.57	±0.80	±0.93	±1.05	±1.15	±1.60	±2.20	±2.50			



ITEM	NAME OF PART	MATERIAL	NOTES
4	Cage	Copper alloy	M3/IN Plated
3	Pin header	Copper alloy	Sn Plated
2	Screw	Steel	M3/Zn Plated
1	Housing	PA66	UL94V-0

UL 标准/UL Standard:	B	C	D
额定电压/电涌/Rated Voltage(V)/Current(A)	300/30	/	300/70
IEC 标准/IEC Standard:			
过压类别/Overvoltage Category/污染等级/Pollution Degree	III/3	III/2	II/2
额定电压/电涌/Rated Voltage(V)/Current(A)	/	450/24	/
工频耐压/Withstanding Voltage(kV/1Min)	/	2.5	/
拧紧扭矩/ Torque Tightening(N·m/Lbin)	M3, 0.5/4.43		
线缆范围/线缆和线材/Wire Range(rigid and flexible)/(mm <sup>2</sup> /AWG)	1.5~4.0/26~10		
间距/Pitch(mm)/线缆范围/Poles	6.35/N=02~16P		
剥线长度/Stripping length(mm)	7-8		
使用温度范围/Operating temperature(°C)	-40~+105		
符合RoHS/符合RoHS/Conform to RoHS	Yes		

MATERIAL:

SURFACE:

NINGBO DEGSON ELECTRICAL CO., LTD

NAME: DG636-6.35-XXP-1Y-00A(H)

MAT NO.:	/
STATUS:	/
APPD: Lon Chh	2020.03.18
CHKD:	/
DRT: Yu JZh	2020.03.18

DRAWING NO.:	DG636-6.35-C01
TYPE:	CUSTOMER DRAWING
SCALE:	2.5:1 SHEET
REV	T0
1/1	

REV	ECN	DESCRIPTION	DRT	DATE
1				
2				
3				
4				

D C B A

1 2 3 4 5 6