









The information provided herein is from CONNELY Electronic Co., Ltd. and is confidential. Any disclosure to a party other than the recipient is prohibited. The intellectual properties and its rights contained herein, including but not limited to, trademarks, patents, copyrights, trade secrets, and technical know-how, are owned exclusively by CONNELY or its affiliates. Unauthorized use or reproduction of any part of this document is strictly prohibited. CONNELY may enforce its intellectual property rights at its own discretion, failures or delays to exercise such rights does not constitute a waiver of such rights.

Dept	Qty
DC	1
ED	1
IE	1
ISO	1
PD	1
R&D	1
SD	1
QA	1
QC	1
QF	1



Dimension

Position	A±0.2	B±0.2	C±0.3	D	E
15	17.90	24.99	30.84	16.33	2.29
26	26.50	33.32	39.14	24.66	2.29
44	40.00	47.04	53.04	38.38	2.29
62	56.50	63.50	69.32	54.84	2.41



REV.	DESCRIPTION	DRAWN	CHECKED	APPROVED
A	NEW RELEASE	YCH 01/10/08'		LJC 01/10/08'
B	DRAWING UPDATE	JLZ 10/08/20'		

- NOTES:
- Electrical characteristics:
    - Contact resistance: 20mΩ Max. Initial.
    - Dielectric withstanding voltage: 500V AC(rms) for 1 minute.
    - Insulation resistance: 1000MΩ Min.
  - Environment characteristics:
    - Temperature range: -40°C~+105°C.
  - Materials:
    - Insulator:PBT+Glass fiber
    - Shell:Steel
    - Contact:Copper alloy
  - Product number code:
 

DS1038-02 - X X X X X X

- Screw DIM. A
- S: Standard(W/O nut)
- 1: 5.00 2: 3.00
- 3: 5.20 4: 4.80
- 5: 5.80 6: 3.80
- Screw type
- A:With screw type
- B:With rivet type
- C:With screw and rivet type
- Contact plating
- 8: Full gold flash
- C: Full 3u" gold
- Shell plating
- N: Fornt shell nickel,Back shell tin
- Color of housing
- B: Black L: Blue W: White
- Connector type
- M: Male F: Female
- No. of contact
- 15,26,44,62

GENERAL TOLERANCE	ANGLE TOLERANCE	PROJECTION	TITLE	Machine Pin H.D-SUB
X. ±0.60	X. ±5°			R/A(9.4mm) Type
.X ±0.38	.X ±3°	UNITS	mm	
.XX ±0.25	.XX ±2°	SHEET SIZE	A4	SERIES DS1038-02 SERIES
DRAWING TYPE	CUSTOMER	<b>晨翔电子有限公司</b> <b>CONNFLY ELECTRONIC CO. LTD</b>		
SCALE	1:1 SHEET 1 OF 1			
DRAWING NO.	C-DS1038-02-XXXXXX-B			