



| REV. | DESCRIPTION | DRAWN | CHECKED | APPROVED |
|------|-------------|--------------|---------|----------|
| A | NEW RELEASE | TQ 05/06/14' | | |

- Specifications:
1. Insulator Material: High Temperature LCP, Color of Black, UL94 V-0.
 2. Insulation Resistance: 5000 MΩ Min.
 3. Max Processing Temp: 280° C for 10 Sec And
230° C for 30 to 60 Sec.
 4. Operating Temp Range: -65° C To +105° C With Tin.
-65° C To +125° C With Gold.
 5. Withstanding Voltage: 600V AC.
 6. Contact Material: Copper Alloy, Plating: Full Gold Flash.
 7. Current Rating: 1A Per Pin Max.
 8. Part Number Code:

DS1064-11 - X.X.X.X.X - 3A

- PLATING LEVEL
3A: 3A GRADE
- PACKING TYPE
B: TUBE
- HOUSING COLOR
B: BLACK
- CONTACT PLATING
8: FULL GOLD
- MOUNTING TYPE
V: STRAIGHT TYPE
- No. OF CONTACTS
26

| GENERAL TOLERANCE | | ANGLE TOLERANCE | |
|-------------------|-------|-----------------|-----|
| X. | ±0.60 | X. | ±5° |
| .X | ±0.38 | .X | ±3° |
| .XX | ±0.25 | .XX | ±2° |

| PROJECTION | TITLE |
|------------|---|
| UNITS | 1.27*2.54mm Box Header V/T Type H=9.65mm |
| SHEET SIZE | SERIES DS1064-11 SERIES |

RECOMMEND PCB LAYOUT
TOLERANCE=±0.05mm


晨翔电子有限公司
CONNFLY® CONNFLY ELECTRONIC CO., LTD

| DRAWING TYPE | CUSTOMER |
|--------------|--------------------|
| SCALE | 1:1 SHEET 1 OF 1 |
| DRAWING NO. | C-DS1064-11-XXXXXX |