



The information provided herein is from CONNELY Electronic Co., Ltd. and is confidential. Any disclosure to a party other than the recipient is prohibited. The intellectual properties and its rights contained herein, including but not limited to, trademarks, patents, copyrights, trade secrets, and technical know-how, are owned exclusively by CONNELY or its affiliates. Unauthorized use or reproduction of any part of this document is strictly prohibited. CONNELY may enforce its intellectual property rights at its own discretion, failures or delays to exercise such rights does not constitute a waiver of such rights.

REV.	DESCRIPTION	DRAWN	CHECKED	APPROVED
A	NEW RELEASE	JLZ 06/06/16'		
B	DRAWING UPDATE	JLZ 05/31/18'		
C	DRAWING UPDATE	JLZ 03/29/20'		

- Notes:
- Electrical Characteristics:
    - Contact Resistance: 30mΩ Max.
    - Dielectric Withstanding Voltage: 1000V AC(rms) For 1 Minute.
    - Insulation Resistance: 500MΩ Min.
    - Current Rating:1.5A.
    - Voltage Rating:125V AC rms.
  - Environment Characteristics:
    - Temperature: -40°C~+85°C.
  - Materials:
    - Contact Material: Copper Alloy.
    - Contact Plating: Gold flash.
    - Insulator Materials: PBT ,UL94-V0.
  - Product Number Code:



Recommend PCB layout(Tolerance:±0.05)



(Series Image-Reference Only)

GENERAL TOLERANCE		ANGLE TOLERANCE	
X.	±0.60	X.	±5°
.X	±0.38	.X	±3°
.XX	±0.25	.XX	±2°

DRAWING TYPE	CUSTOMER		
SCALE	1:1	SHEET	1 OF 1
DRAWING NO.	C-DS1130-02-XXXXX-C		

PROJECTION	TITLE
	PCB Jack 8 Positions 1*6 Port W/ Shell 3.68mm Type
UNITS	SERIES
mm	DS1130-02 SERIES

**晨翔电子有限公司**  
 CONNELY CONNELY ELECTRONIC CO., LTD