



REV.	DESCRIPTION	DRAWN	CHECKED	APPROVED
A	NEW RELEASE	JLZ 10/27/16'		

NOTES:

- ELECTRICAL CHARACTERISTICS:
  - CONTACT RESISTANCE: 30mΩ Max.
  - DIELECTRIC WITHSTANDING VOLTAGE: 1000V AC(rms) FOR 1 MINUTE.
  - INSULATION RESISTANCE: 1000MΩ Min.
  - VOLTAGE RATING: 125V.
  - CURRENT RATING: 1.5A.
  - VOLTAGE(LED): 2.4V MAX.
- ENVIRONMENT CHARACTERISTICS:
  - TEMPERATURE: -0°C~+70°C.
- MATERIALS:
  - HOUSING: PA66 BLACK UL94 V-0
  - INSERT: PBT BLACK YELLOW UL94 V-0
  - CONTACT: COPPER ALLOY
  - CONTACT PLATING: SELECTIVE GOLD, 6u" MIN IN CONTACT AREA
- PRODUCT NUMBER CODE:  
DS1134-09-X X X X X

- Housing Materials  
N: Nylon
- Contact Plating  
S: Selective 6u" Gold
- Housing Color  
B: Black
- No. Of Contacts  
8: 8p8c
- Connector Type  
S: Socket

Tel: 86-574-63508787  
 Fax: 86-574-63510817  
 E-mail: sale@connfly.com  
 http://www.connfly.com  
 Add: East Industry Zone KuangYan  
 Town Cixi Ningbo China  
 P.O: 315333

Pi n	Yellow	Green	
P9	+	P11	+
P10	-	P12	-

GENERAL TOLERANCE		ANGLE TOLERANCE	
X.	±0.60	X.	±5°
.X	±0.38	.X	±3°
.XX	±0.25	.XX	±2°

DRAWING TYPE	CUSTOMER
SCALE	1:1 SHEET 1 OF 1
DRAWING NO.	C-DS1134-09-XXXX-A

PROJECTION	TITLE
	RJ45 ICM(10/100 Base-T 1 Port)
UNITS	mm
SHEET SIZE	A4
SERIES	DS1134-09 SERIES

晨翔电子有限公司  
 CONNFLY CONNFLY ELECTRONIC CO. LTD