



REV.	DESCRIPTION	DRAWN	CHECKED	APPROVED
A	NEW RELEASE	JLZ 12/27/14'	~	

- NOTES:**
- Materials:**
 - Insulator:**
Cover: PBT 30% GF, UL94 V-0 Rated.
Housing: PBT 30% GF, UL94 V-0 Rated.
 - LED Contact:** Copper Alloy, Plating Gold Over Nickel,
Wire Trap: Copper Alloy, Plating Tin Over Nickel.
 - Specifications:**
 - Voltage-Max:** 600V DC.
 - Application wire range:**
 - single solid wire: 0.3-0.75mm².
 - stranded type wire: 22-18AWG.
 - 3.1cm +2.0/-0.0cm strip length is recommended.
 - Mount holder using M3 or 4-40 screws(2),
0.2 N/m min 0.4 N/m max torque.**
 - Product Number Code:**

DS1137-11 - X X X X

- Contact plating
- 8: Full gold flash.
- Housing Color
- W: White
- Connector Type
- F: Female
- No. of positions
- 02: 2p

Tel: 86-574-63508787
 Fax: 86-574-63510817
 E-mail: sale@connfly.com
 http://www.connfly.com
 Add: East Industry Zone KuangYan
 Town Cixi Ningbo China
 P.O. 315333

M3 OR 4-40 TAPPED HOLES
 TORQUE SCREWS 0.2-0.4N/m MAX.

RECOMMENDED MOUNTING DIMENSIONS

GENERAL TOLERANCE		ANGLE TOLERANCE		PROJECTION		TITLE
X.	±0.60	X.	±5°	UNITS	mm	LED LAMP HOLDER INSERT WIRE BIG TYPE SERIES
.X	±0.38	.X	±3°	SHEET SIZE	A4	SERIES DS1137-11 SERIES
.XX	±0.25	.XX	±2°	晨翔电子有限公司 CONNFLY CONNFLY ELECTRONIC CO., LTD		
DRAWING TYPE CUSTOMER		SCALE		SHEET		1 OF 1
DRAWING NO.		C-DS1137-11-XXXXX-A				